

52" Non Woven Contract Wallcovering

Physical Properties

- **30% post-consumer recycled content**
 - Content—natural fibers, man-made fibers
- Weight 11.2 oz. PLY / 347.3 G/PLM 7.5. oz. PSY / 254.3 G/PSM
Backing Osnaburg
Width 52" / 132 cm

Meets or exceeds Federal Specification CCC-W-408D physical characteristics for Type II Wallcovering

Fire Safety

- Class "A" Fire Rated – Tested in accordance with ASTM E-84 Tunnel Test
- Flame Spread 25 / Smoke Developed 5

Environment & Health

- Meets California Section 01350 IAQ test requirements for wallcovering
- Can contribute to LEED MR 4.1 and MR 4.2 for recycled content
- Can contribute to LEED EQ 4.1 point for low-emitting materials, adhesives, and sealants, if used with low VOC adhesives
- Can contribute to LEED MR 5.1 for regional materials
- Can contribute to LEED MR 7 for certified wood

Anti-Microbial Features

This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

Warranty

5 year warranty against manufacturing defects. Additional information is available at www.SymphonyWallcovering.com Eco-Innovation for the Contract Market



The mark of responsible forestry
Cert no. SGS-COC-004621
© 1996 Forest Stewardship Council A.C.
Printed on FSC certified paper