

## 52" Non Woven Contract Wallcovering

### Physical Properties

---

- **30% post-consumer recycled content**
  - Content—natural fibers, man-made fibers
- Weight 11.2 oz. PLY / 347.3 G/PLM 7.5. oz. PSY / 254.3 G/PSM  
Backing Osnaburg  
Width 52" / 132 cm

Meets or exceeds Federal Specification CCC-W-408D physical characteristics for Type II Wallcovering

### Fire Safety

---

- Class "A" Fire Rated – Tested in accordance with ASTM E-84 Tunnel Test
- Flame Spread 25 / Smoke Developed 5

### Environment & Health

---

- Meets California Section 01350 IAQ test requirements for wallcovering
- Can contribute to LEED MR 4.1 and MR 4.2 for recycled content
- Can contribute to LEED EQ 4.1 point for low-emitting materials, adhesives, and sealants, if used with low VOC adhesives
- Can contribute to LEED MR 5.1 for regional materials
- Can contribute to LEED MR 7 for certified wood

### Anti-Microbial Features

---

This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

### Warranty

---

5 year warranty against manufacturing defects. Additional information is available at [www.SymphonyWallcovering.com](http://www.SymphonyWallcovering.com) Eco-Innovation for the Contract Market